

Moose Jaw Aerial Lift Safety Training

Moose Jaw Aerial Lift Safety Training - Each and every year, there are around 26 construction fatalities due to the utilization of aerial lifts. Most of the craftsmen killed are laborers, electrical workers, ironworkers, carpenters or painters. The majority of the fatalities are caused by electrocutions, falls and tip-overs. The greatest hazard is from boom-supported lifts, like for instance bucket trucks and cherry pickers. Most fatalities are related to this kind of lift, with the rest involving scissor lifts. Other hazards comprise being struck by falling objects, being thrown out of a bucket, and being caught between the lift bucket or guardrail and a thing, such as a steel beam or joist.

In order to operate an aerial lift safely, carry out an inspection on the following items prior to utilizing the device: emergency and operating controls, safety devices (e.g., outriggers and guardrails), personal fall protection gear, and wheels and tires. Check for possible leaks in the air, fuel-system, hydraulic fluid. Check the device for missing or loose parts.

The location where the device will be utilized should be thoroughly inspected for potential dangers, such as holes, bumps, debris and drop-offs. Overhead power lines must be avoided or closely monitored. It is recommended that aerial lift devices be used on level, stable surfaces. Never work on steep slopes which go beyond slope restrictions specified by the manufacturer. Even on a level slope, brakes, wheel chocks and outriggers must be set.

Employers are required to provide maintenance mechanics and aerial lift operators with the proper manuals. Operators and mechanics should be trained by a licensed individual experienced with the relevant aerial lift model.

Aerial Lift Safety Tips:

- o Close doors or lift platform chains prior to operating.
- o Do not lean over or climb on guardrails. Stand on the platform or floor of the bucket.
- o Make use of the provided manufacturer's load-capacity restrictions.
- o When working near traffic, use appropriate work-zone warnings, like signs and cones.

If correct procedures are followed, electrocutions are avoidable. Stay at least 10 feet away from whatever power lines and qualified electricians must de-energize and/or insulate power lines. Workers must make use of personal protective tools and equipment, like for instance a bucket which is insulated. Then again, an insulated bucket does not protect from electrocution if, for instance, the worker touches another wire providing a path to the ground.

Falls are preventable if the person working remains secure in guardrails or inside the bucket by using a positioning device or a full-body harness. If there is an anchorage within the bucket, a positioning belt together with a short lanyard is acceptable.

Tip-overs are preventable by following the manufacturer's directions. Unless otherwise specified by the manufacturer, never drive whilst the lift platform is elevated. Adhere to the vertical and horizontal reach limitations of the device, and never go beyond the specified load-capacity.