

Moose Jaw Boom Lift License

Moose Jaw Boom Lift License - In order to operate an aerial boom lift, operators must be qualified through training which can be obtained using both classroom sessions and practical training and by obtaining a boom lift license. Instruction must be given with respect to the kind of aerial lift which would be used on the job. A License is needed for anyone who works on or operates an aerial boom lift.

Vehicle-mounted aerial devices include the following work vehicles: aerial ladders, extensible boom platforms, articulating boom platforms, vertical towers, and whichever combination of these types.

When making use of a boom lift, there are a few basic safety regulations which apply to all boom lifts. Safety of the worker is a main concern whilst they are working in the basket. The worker must always wear a body harness and lanyard, attaching it to the basket or boom. Never tie off to a structure, equipment or an adjacent pole. Workers should stand on the basket floor, and never sit or climb on the basket edge. The manufacturer's load restrictions must be followed.

Lift operators need to be authorized to operate an aerial lift. The manufacturer's instruction manual must be kept within the lift and the operator has to know all aspects of that specific unit. Operators are responsible for ensuring that safety measures are followed in operating the lift. Testing lift controls everyday must be carried out. Position outriggers and set brakes (if they are used) on pads or a stable surface. If working on a slope, utilize wheel chocks.

The aerial lift vehicle must never be moved whilst a worker is in the basket of an elevated boom, unless they are making use of equipment that are particularly designed for this. Articulating boom and extensible boom platforms utilized as employees carriers must have plainly marked, accessible, upper controls. Except in emergency situations, lower controls must not be utilized to override upper controls unless the person inside the lift gives consent.

While working from an aerial lift, do not wear pole or tree climbers.

The insulated part of the aerial lift must not be altered.

Ensure that the booms are carefully inspected, that the machinery is properly cradled and the outriggers are in the stowed position before moving.

When operating a boom lift next to power lines, make certain that the lines are di-electrically tested according to local regulations.